




14/4 In-Wall + Direct Burial

14 AWG, 4 Conductors, stranded oxygen free copper. General Purpose (CL3) rated for indoor residential installation in walls and risers (no plenums) and indoor commercial installation in walls (no risers or plenums). Direct Burial rated for installation in-ground without conduit. UL Listed.

<https://www.voltive.com/products/voltive-14-4-max-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Testing Laboratory	UL
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Direct Burial?	Yes
Sunlight Resistant?	No
Materials & Construction	UL 13
RoHS?	Yes

Insulation

Colors	Red, Black, White, Green
Material	Polyvinyl Chloride (PVC)
Average Thickness (mm)	0.35 ± 0.08
Minimum Thickness (mm)	0.28
Outer Diameter (mm)	2.70 ± 0.20
Minimum Resistance	100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Conductors

Gauge	14AWG
Count	4
Material	Oxygen Free Copper
Outer Diameter (mm)	1.86
Strand Count	105
Strand Diameter (mm)	0.157
Maximum Resistance	8.60 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness (mm)	0.88 ± 0.10
Minimum Thickness (mm)	0.62
Outer Diameter (mm)	8.40 ± 0.30
Minimum Bend Radius (mm)	126
Paper Tissue?	Yes
Ripcord	Nylon (1000D)
Marking A	VOLTIVE 14AWG 4C - E516774-41 (UL) CL3 DIRECT BURIAL 75C - XXX USED / XXX REMAINING
Marking B	V-XXXX - MM/DD/YY - VOLTIVE.COM - XXX USED / XXX REMAINING

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1025	Black	100ft	Spool	850001725378	9.0 lbs	7.9 x 7.9 x 5.0	View
V-1027	Black	250ft	Box	850001725439	24.2 lbs	13.9 x 10.2 x 13.5	View
V-1029	Black	500ft	Box	863831000492	45.3 lbs	16.5 x 10.2 x 15.9	View
V-1026	White	100ft	Spool	850001725385	9.0 lbs	7.9 x 7.9 x 5.0	View
V-1028	White	250ft	Box	850001725606	24.2 lbs	13.9 x 10.2 x 13.5	View
V-1030	White	500ft	Box	863831000454	45.3 lbs	16.5 x 10.2 x 15.9	View