




12/2 In-Wall + Direct Burial

12 AWG, 2 Conductors, stranded oxygen free copper. General Purpose (CL3) rated for indoor residential installation in walls and risers (no plenums) and indoor commercial installation in walls (no risers or plenums). Direct Burial rated for installation in-ground without conduit. UL Listed.

<https://www.voltive.com/products/voltive-12-2-max-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Testing Laboratory	UL
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Direct Burial?	Yes
Sunlight Resistant?	No
Materials & Construction	UL 13
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness (mm)	0.42 ± 0.08
Minimum Thickness (mm)	0.34
Outer Diameter (mm)	3.20 ± 0.20
Minimum Resistance	100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Conductors

Gauge	12AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter (mm)	2.34
Strand Count	65
Strand Diameter (mm)	0.251
Maximum Resistance	5.41 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness (mm)	0.88 ± 0.10
Minimum Thickness (mm)	0.62
Outer Diameter (mm)	7.80 ± 0.50
Minimum Bend Radius (mm)	117
Paper Tissue?	Yes
Ripcord	Nylon (1000D)
Marking A	VOLTIVE 12AWG 2C - E516774-41 (UL) CL3 DIRECT BURIAL 75C - XXX USED / XXX REMAINING
Marking B	V-XXXX - MM/DD/YY - VOLTIVE.COM - XXX USED / XXX REMAINING

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1009	Black	100ft	Spool	850001725262	7.3 lbs	7.9 x 7.9 x 5.0	View
V-1011	Black	250ft	Box	850001725415	19.5 lbs	11.6 x 9.9 x 11.8	View
V-1013	Black	500ft	Box	850001725088	37.5 lbs	16.5 x 10.2 x 15.9	View
V-1010	White	100ft	Spool	850001725279	7.3 lbs	7.9 x 7.9 x 5.0	View
V-1012	White	250ft	Box	850001725422	19.5 lbs	11.6 x 9.9 x 11.8	View
V-1014	White	500ft	Box	850001725002	37.5 lbs	16.5 x 10.2 x 15.9	View